

# Snap-in Tubeless Tire Valves

TR-412



Snap-in Tire Valves for  
0.453" Rim Holes

TR-413



TR-414



TR-418



TR-423



Schrader snap-in tubeless tire valves are the same top quality valves used as original equipment on all makes of cars since 1955. Made with a special rubber compound to resist ozone damage and prevent premature deterioration caused by rim hole compression, heat, and cold. Maximum inflation pressure 65 PSI.

Dimensions and specifications on back.

TR-415



Snap-in Tire Valves for  
0.625" Rim Holes

TR-600




High Pressure Snap-in  
Tire Valves for 0.453"  
Rim Holes

TR-602



TR-801



High Pressure Snap-in  
Tire Valves for 0.625"  
Rim Holes

Tubeless snap-in tire valves for high pressure applications are available in two varieties. The 600 series is designed for a maximum inflation pressure of 80 PSI, the 800 series has a maximum inflation pressure of 100 PSI.



**SCHRADER-USA** 205 FRAZIER ROAD ▶ ALTAVISTA, VA 24517

CUSTOMER SUPPORT LINE // 1.800.288.1804 x8817 ▶ SCHRADERINTERNATIONAL.COM

# Snap-in Tubeless Tire Valves

Schrader snap-in tubeless tire valves are the same top quality valves used as original equipment on all makes of cars since 1955. Made with a special rubber compound to resist ozone damage and prevent premature deterioration caused by rim hole compression, heat, and cold. Maximum inflation pressure is 65 PSI.

<b>Snap-in Tire Valves for 0.453" Rim Holes</b>			
Schrader Part Number	Tire & Rim Number	Effective Length	Max. PSI
3141200042	TR412	0.875"	65
3141300042	TR413	1.25"	65
3141400042	TR414	1.500"	65
3141800042	TR418	2.000"	65
3142300142	TR423	2.500"	65

<b>Snap-in Tire Valves for 0.625" Rim Holes</b>			
Schrader Part Number	Tire & Rim Number	Effective Length	Max. PSI
3141500142	TR415	1.250"	65

Tubeless snap-in tire valves for high pressure applications are available in two varieties. The 600 series is designed for a maximum inflation pressure of 80 PSI, the 800 series has a maximum inflation pressure of 100 PSI.

<b>High Pressure Snap-in 600 series for 0.453" Rim Holes</b>			
Schrader Part Number	Tire & Rim Number	Effective Length	Max. PSI
3160000042	600HP	1.270"	80
291460	602HP	2.000"	80

<b>High Pressure Snap-in 800 series for 0.625" Rim Holes</b>			
Schrader Part Number	Tire & Rim Number	Effective Length	Max. PSI
3180100042	801HP	1.310"	100

*Due to the variety of operating conditions or applications, the customer is responsible to perform their own testing to insure performance, safety and warning requirements for the intended application.*



**SCHRADER-USA** 205 FRAZIER ROAD ▶ ALTAVISTA, VA 24517

CUSTOMER SUPPORT LINE // 1.800.288.1804 x8817 ▶▶ SCHRADERINTERNATIONAL.COM

Snap-in tubeless tire valves - 062116