



- 36V AC
- LED Lighting
- DC/DC Converter
- Adjustable Seats
- Tilted Steering Wheel
- Regenerative Braking
- 137 inch Turning Radius
- 10 inch Larger Operator's Compartment



THE NEXT LEVEL OF COMFORT & PERFORMANCE



Taylor-Dunn is proud to introduce our new line of BIGFOOT electric vehicles. The standard features include a 10 inch larger ergonomically designed operator's compartment, tilted steering, and sliding adjustable seats, which increases leg room and reduces operator fatigue.

Additional standard features include our GT Drive system, 36 volt AC power, Smart View Display, hydraulic disc brakes, recessed tie-downs, 12 gauge smooth skin, unitized steel body, DC/DC converter, cupholders, and a heavy duty all gear drive train that ensures reliability and low maintenance costs.

Visit our website for additional vehicle images, videos, information and custom modifications at www.taylor-dunn.com.

VOLTAGE	36 volt	
SPEED	12 mph	19 km/h
RANGE	up to 30 mi	up to 48 km
LOAD CAPACITY	3,000 lb	1361 kg
BED SIZE (W x L)	44 x 77 in	1117 x 1955 mm
TURNING RADIUS	137 in	3480 mm

Based on Standard Configuration

Typical Capacity: Actual load capacity depends on application and vehicle configuration.

FEATURES & BENEFITS:

- Zero emissions
- Recessed tie-downs
- Smooth and quiet operation
- Dual USB port for charging devices
- 10 in. larger operator's compartment
- Customizable to fit your application



Dual USB Port



Adjustable Seats



Dual Cup Holders



Recessed Tie-downs



Large Compartment



LED Lighting




Tilted Steering



**36V**


PERFORMANCE

LOAD CAPACITY	3,000 lb	1361 kg
MAX SPEED (UNLOADED)	12 mph	19.3 km/h
TURNING RADIUS	137 in	3480 mm
TOW CAPACITY	7,500 lb	3402 kg




DIMENSIONS

OVERALL LENGTH	130.5 in	3314 mm
OVERALL WIDTH	44 in	1117 mm
HEIGHT (- cab)	51.5 in	1308 mm
HEIGHT (+ cab)	73 in	1854 mm
WHEEL BASE	62 in	1574 mm
GROUND CLEARANCE	5.5 in	139 mm
BED SIZE	44 x 77 in	1117 x 1955 mm



POWER SUPPLY / DRIVE TRAIN

MOTOR	7.5 hp, 5.5 kW AC
SYSTEM VOLTAGE	36 Volt
DRIVE AXLE	Helical Gear, Oil Bath Transaxle, GT Automotive Differential
BATTERIES	210 amp-hour, T605, 6 each, 6 Volt
CHARGER	Built-in, 36V, 115 VAC / 60 Hz, 1kW w/ Interlock
CONTROLLER	Solid State Self Diagnostic AC Speed Controller

**GT Automotive Drive**

CHASSIS

FRAME	12 Gauge, Smooth Skin, Unitized, Fully Welded, Steel
STEERING	Rack and Pinion
SUSPENSION	Multi-leaf Springs, Front and Rear
BRAKES	Rear Hydraulic Disc Brakes with Hand Parking Brake
BUMPERS	Heavy Duty Steel Integrated Front & Rear
TIRES	5.70 x 8, Load Range C, Pneumatic

GENERAL

UNIT WEIGHT	1,450 lb	658 kg
SEATS	Black Adjustable Bucket Seats, Driver's Seat Electrical Interlock, 2 Person	
INSTRUMENTATION	Smart View Display, Reverse Alarm, Forward / Off / Reverse Selector, Key Switch, Light Switch, High / Low Speed Switch, Electric Horn, Emergency Power Cut-off Switch, DC/DC Converter, Dual USB Port	
LIGHT ACCESSORIES	Dual LED Headlights, Taillights and Brake Lights	
CONFORMANCE	Type E, ANSI B56.8, OSHA 1910.178	

OPTIONS

- FOLD-AWAY SEATS
- STEEL CAB / DOORS
- PORTABLE CHARGER
- STROBE LIGHT
- DIAMOND PLATE DECK
- ALUMINUM DROP-DOWN SIDES
- BATTERY WATERING SYSTEM
- LOCKABLE CARGO BOX
- LIFT OUT BATTERY BOX
- DIRECTIONAL SIGNALS
- FRONT DISC BRAKES
- VARIOUS HITCHES
- UNDERCOATING
- GALVANIZED FRAME
- OPTIONAL PAINT COLORS

Specifications, standard equipment, accessories and modifications are subject to change without notice.